

RT125



Flexible High Performance Epoxy Adhesive

Description

RT125 is the industry standard adhesive for high performance cable harness assemblies.

Benefits

- Excellent flexibility giving high shear and peel strengths
- Outstanding chemical and fluid resistance
- Will operate up to 150°C
- Will also bond metals, glass, wood, rubbers and many plastics
- Supplied in DuoSyringe for easy application
- Standard size is 50ml, with associated mixing nozzles and dispenser guns

Typical Properties

Curing

Work life at 23°C:	90 minutes
Time to handling at 23°C:	24 hours
Time to full cure at 23°C:	7 days
Time to full cure at 85°C:	2 hours

Typical Performance (measurements at 23°C)

Lap Shear (Al / Al)	20 MPa
Peel Strength (XLPE/XLPE)	370 N / 25mm
Peel Strength after Thermal Shock (4hrs@215°C)	370 N / 25mm
Dynamic Shear (Backshell/boot/cable. Shell size 22)	520 N
Solvent resistance (De-icing fluid, Petrol, Lubricating oil, Hydraulic fluid)	Excellent
Operating Temperature	-75°C to +150°C

Conforms to the requirements of VG95343 Pt 15 and BS G 198 Part 5

Colour

Black

Related Products

- The ShieldFast® Range
- RT183 electrically conductive epoxy adhesive

Issue 5 - March 2005

Resintech Limited warrants only that it's products meet the specifications stated herein. Typical properties where stated are to be considered as representative of the current production and should not be treated as specifications. While the information presented is believed to be true and reliable, users are advised to conduct sufficient investigations to ensure the suitability of any product for its intended use. Resintech Limited cannot accept any responsibility for loss or damage that may result from the use of this information.

Resintech Limited

Horcott Industrial Estate, Fairford, Gloucestershire, GL7 4BX, United Kingdom

t: +44 (0)1285 712755 f: +44 (0)1285 712999 e: technical@resintech.co.uk w: www.resintech.co.uk